

First Quarter 2021 Outfall and In-Stream Sampling T.F. Green Airport

Prepared by: Rhode Island Airport Corporation

April 2021

Background

The RIPDES permit identifies major and minor outfalls at PVD. Outfalls 001A, 002A, 003A, 004A and 013A discharge to tributaries of Warwick Pond. Outfalls, 006A, 007A, 008A and 009A discharge to tributaries of Buckeye Brook downstream of Warwick Pond. Outfalls 010A, 011A, and 012A discharge to Tuscatucket Brook. Major outfalls, 002A, 003A, 008A, and 010A, are those outfalls which receive or may receive drainage from areas where aircraft deicing fluid is applied. Sampling for these major outfalls is defined at Part I.A.1 of the permit. Minor outfalls drain taxiways, runways and other paved services. Outfall 005A was combined with Outfall 006A during construction of Runway 34 Safety Area Improvements. Sampling for these minor outfalls is defined at Part I.A.2. of the permit. Additional sampling requirements are defined at Part I.A.5. and Parts I.C. and I.D. Table 1 lists parameters sampled.

Part I.B.4.h describes water quality monitoring requirements for receiving water bodies. Stream monitoring is conducted at four locations: the inlet to Warwick Pond at Lake Shore Drive; the outlet to Warwick Pond at the south end of Lake Shore Drive; Buckeye Brook at West Shore Road; and Old Mill Creek at Tidewater Drive. These sample locations are identified as BB-02, BB-03, BB-04 and BB-07 (respectively) to maintain consistency with previous sampling studies in the Buckeye Brook watershed. Figure 1 identifies outfall and in-stream sampling locations.

Industrial activities at PVD with the potential to impact stormwater quality include the use of glycol-based Aircraft Deicing and Anti-icing Fluids (ADFs/AAFs) and pavement deicers. Only propylene glycol (PG)-based ADFs/AAFs are used at PVD.

On March 18, 2021 approximately 60 gallons of deicing fluid was applied to 3 aircraft. Approximately 7,000 gallons of fluid were diverted to storage at the Deicing Treatment Facility.

Pavement deicers used at PVD include solid sodium formate, and liquid potassium acetate. No liquid or solid pavement deicer was applied to runways and taxiways during this sampling event.

Summary of Storm

First Quarter (January 1 through March 31) sampling includes the major outfalls (002A, 003A, 008A and 010A) hourly for twelve hours and in-stream sampling locations (BB-02, BB-03, BB-04 and BB-07) every four hours for forty eight hours. The sampling began upon a precipitation event of sufficient magnitude and subsequent to aircraft deicing as specified in the RIPDES permit.

Light rain began falling around 1:00 PM on March 18, 2021. Sampling commenced at 5:00 PM subsequent to measurable accumulation. Outfall sampling continued until approximately 4:00 AM on March 19, 2021. In-stream sampling continued until 4:00 PM on March 20, 2021.

A total of 1.01 inches of precipitation (as water equivalent) was measured at PVD between March 18 and March 20, 2021. Precipitation data is summarized in Table 2.

Summary of Flow

Flow meters are installed at three of the major outfalls: 002A, 003A, and 008A. Continuous flow measurements during the 12 hours of sampling were made using these Isco 2150 area velocity meters programmed to measure level and velocity at 15 minute increments. No flow meters are installed at minor outfalls or at outfall 010A, as it is off airport property.

Maximum daily and average monthly flows for outfalls 002A, 003A, and 008A were calculated using measured data. Estimated runoff volumes calculated using drainage area and depth of precipitation for all outfalls are presented in Table 3.

Sample Collection

For the First Quarter the major outfalls (002A, 003A, 008A, and 010A) were sampled hourly for twelve hours, beginning at 5:00 PM on March 18, 2021, subsequent to measurable accumulation. Outfall sampling continued until approximately 4:00 AM on March 19, 2021. Instream sampling continued until 4:00 PM on March 20, 2021.

A total of 1.01 inches of precipitation (as water equivalent) was measured at PVD between March 18 and March 20, 2021.

Receiving water sampling in Buckeye Brook (BB-02, BB-03, BB-047 and BB-078) commenced concurrent with the outfall sampling. Downstream samples were collected every four hours for 48 hours. During downstream sample collection, no discoloration, foaming, or unusual odors were observed by sampling personnel.

All samples were collected and decanted into sample bottles. The bottles were then placed in ice in a cooler for transport to the laboratory for analysis. Because of the short sample holding time for Fecal Coliform, all samples collected in the first three hours were transported to the laboratory immediately following the third hour of sampling.

At the major outfalls and in-stream sampling measurements for temperature, pH, dissolved oxygen (DO), and specific conductance were taken and recorded in the field. Dissolved oxygen percent saturation was also measured at in-stream locations.

Sampling Results

A summary of sampling results for major outfalls are presented in Tables 4 and 5. In-stream sampling results are presented in Tables 6 and 7.




TABLE 1 LABRATORY ANALYTICAL PARAMETERS T.F. GREEN AIRPORT WARWICK, RHODE ISLAND FIRST QUARTER 2021

Sample Identification	Hours 1-3	Hours 4-12
OF-002A, OF-003A, OF-008A, OF- • Fecal coliform	• Fecal coliform	BOD, surfactants
010A	BOD, TSS, Surfactants	• COD, TOC
	• COD, TOC	Propylene glycol
	• Oil & grease -1664	Dissolved Potassium and Sodium
	Propylene glycol	• Total Metals (aluminum, chromium, copper, iron, lead, and zinc)
	 Dissolved Potassium and Sodium 	
	• Total Metals (aluminum, chromium, copper,	
	iron, lead, and zinc)	
Sample Identification	$\mathbf{H_0}$	Hours 4, 8, 12, 16, 20, 24, 28, 32, 36, 40, 44, and 48
BB-02, BB-03, BB-04, BB-07	• BOD	
	·COD	
	Propylene glycol	

Note: Outfall and BB field measurements for pH, Specific Conductance, Temperature, and Dissolved Oxygen. BB includes DO % saturation BOD -biological oxygen demand COD -chemical oxygen demand

TOC -total organic carbon TSS -total suspended solids

TABLE 2
PRECIPITATION AMOUNTS
T.F. GREEN AIRPORT
WARWICK, RHODE ISLAND
FIRST QUARTER 2021

Date	Total Precipitation (water equivalent in inches)	Snowfall (inches)
March 15, 2021	0	0
March 16, 2021	0	0
March 17, 2021	0	0
March 18, 2021	1.0	0
March 19, 2021	0.1	T
March 20, 2021	0	0

Sampling commenced at 17:00 on March 18, 2021 Major outfall sampling ended at 04:00 on March 19, 2021 Buckeye Brook sampling ended at 16:00 on March 20, 2021

TABLE 3 PVD RUNOFF VOLUME CALCULATION T.F. GREEN AIRPORT WARWICK, RHODE ISLAND FIRST QUARTER 2021

3/18-3/20/2021 Precip (inches):

1.01

7.86	PVD Storm			
Drainage	Water	Receiving	Drainage	
Basin ID	Discharge	Water	Area (ac)	gal precip
1	Outfall 001A	Warwick Pond	5.9	161,801
2	Outfall 002A	Warwick Pond	93.4	2,561,395
3	Outfall 003A	Warwick Pond	119.8	3,285,386
4	Outfall 004A	Warwick Pond	30.1	825,460
6	Outfall 006A	Buckeye Brook	10.7	293,436
6B	Outfall 006B	Buckeye Brook	1.5	41,136
6C	Outfall 006C	Buckeye Brook	0.8	21,939
6D	Outfall 006D	Buckeye Brook	0.7	19,197
7	Outfall 007A	Buckeye Brook	9.6	263,270
.7B	Outfall 007B	Buckeye Brook	1.2	32,909
8	Outfall 008A	Buckeye Brook	240.6	6,598,196
9	Outfall 009A	Buckeye Brook	38.4	1,053,079
		Tuscatucket		
10	Outfall 010A	Brook	26	713,022
		Tuscatucket		
11	Outfall 011A	Brook	14	383,935
		Tuscatucket		-
12	Outfall 012A	Brook	46.4	1,272,470
13	Outfall 013A	Warwick Pond	28	
			667.1	18,294,500

TABLE 4 ANALYTICAL RESULTS MAJOR OUTFALLS T.F. GREEN AIRPORT WARWICK, RHODE ISLAND FIRST QUARTER 2021

	ar a	towers Sold Sta	600 8 28 8 4 8	Major (Outfalls			
Parameter	Outfal	I 002A	Outfal	I 003A	Outfal	I 008A	Outfal	I 010A
	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily
Flow (gpd) ^{1, 8}	361,537	1,113,459	542,305	1,670,188	4,684,405	11,873,207	1,426,044	1,426,044
Oil & Grease (mg/l) ⁵		1.7		1.3		1.2		1.7
TSS (mg/l) ^{4, 5}	15.8	24	8.2	12.0	15.3	23.0	17.1	25.0
Fecal Coliform (MPN/100ml) 7,5	20.4	33	11.0	11.0	11.0	11	11.9	49
BOD ₅ (mg/l) ^{2, 6}	10.7	24	5.5	26	1.4	16	3.0	10
Propylene Glycol (mg/l) 2, 6	ND	ND	1.1	20	1.3	11	ND	ND
COD (mg/l) ^{2, 6}	19.4	47	11.4	42	6.7	36	8.8	57
Dissolved Potassium (mg/l) 2,6	3.41	5.20	2.96	5.30	3.33	10.00	2.17	4.40
Dissolved Sodium (mg/l) 2,6	0.91	4.30	3.45	9.70	7.05	23.00	15.79	32.00
Surfactants (ug/l) 2, 6	104.8	320	85.5	210	34.77	210	27.5	190.0
Dissolved Oxygen (mg/l) ^{2, 3}	9.26	10.24	9.75	10.45	10.68	11.37	11.20	11.84
TOC (mg/l) ^{2, 6}	6.34	13.0	4.11	9.7	3.48	9.7	3.24	5.5
Total Aluminum (ug/l) 2,6	182.3	300	285.8	430	289.1	430	170.8	560
Total Chromium (ug/l) 2,6	0.55	1.3	0.2	1.0	2.46	4.6	1.23	4.2
Total Copper (ug/l) ^{2, 6}	2.19	11	2.79	14	ND	ND	ND	ND
Total Iron (mg/l) ^{2, 6}	7.73	16.0	2.06	4.9	1.73	3.9	1.97	5.6
Total Lead (ug/l) ^{2, 6}	3.35	6.3	0.04	1.8	2.01	3.6	0.53	2.0
Total Zinc (ug/l) 2, 6	ND	ND	ND	ND	ND	ND	ND	ND

¹ Results reported as average monthly were determined using the arithmetic average of measurement made every 15 minutes during the 12 hours of sampling. Results reported as maximum daily was the maximum flow measurements over the 12 hours of sampling. Both reported values were converted from GPM to GPD reflecting a 24 hour day

BOD₅ Biological oxygen demand 5-day test

COD Chemical oxygen demand

TOC Total organic carbon

TSS Total suspended solids

gpd gallons per day

mg/l milligrams per liter

ug/l micrograms per liter

ND - Non-Detect

² Results reported as maximum daily were the maximum of the 12 samples collected during the 12 hours of sampling.

³ Results reported as average monthly were determined using the arithmetic average of the 12 samples collected during the 12 hours of sampling.

⁴ Results reported as average monthly were determined using the arithmetic average of the 3 samples collected (when available) during the first 3 hours of sampling.

⁵ Results reported as maximum daily were the maximum of the 3 samples collected (when available) during the first 3 hours of sampling

⁶ Results reported as average monthly were determined by using a flow-weighted average of the 12 samples collected during the 12 hours of sampling.

⁷ Results reported as average monthly were determined by using a geometric mean of the 3 samples collected (when available) during the 3 hours of sampling

⁸ Outfall 010A does not have a flow meter installed. Therefore, flow was calculated arithmetically utilizing the Outfall drainage area, storm intensity, and duration.

TABLE 5 FIELD ANALYTICAL RESULTS MAJOR OUTFALLS T.F. GREEN AIRPORT WARWICK, RHODE ISLAND **FIRST QUARTER 2021**

51.4		51.0		50.3		51.9		Temperature (°F)
6.8	6.3	6.8	6.3	6.8	6.4	6.7	6.4	pН
Daily ²	Daily¹	Daily ²	Daily¹	Daily²	Daily¹	Daily ²	Daily¹	
Maximum	Minimum	Maximum	muminiM	Maximum	Minimum	Maximum	Minimum	רמומוווסנסו
010A	Outfall	008A	Outfall 008A	Outfall 003A	Outfall	Outfall 002A	Outfal	Doromotor
)⊔tfalls	Major Outfalls				

Bold text indicates exceedance of permit standards

Reported values are from laboratory analsis. Field pH measurements were taken but not used for this report

¹ results reported as minimum daily were the minimum of the samples collected during the 12 hours of sampling.
² results reported as maximum daily were the maximum of the samples collected during the 12 hours of sampling.

TABLE 6 ANALYTICAL RESULTS BUCKEYE BROOK T.F. GREEN AIRPORT WARWICK, RHODE ISLAND FIRST QUARTER 2021

	BB-02	-02	BB-03	-03	BB-04	-04	BB	-07
Parameter	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily	Average Monthly	Maximum Daily
Conductivity (umhos/cm) 1,2	279.7	336.5	312.1	382.9	294.5	344.9	268	309
BOD ₅ (mg/l) ^{1, 2}	3.7	9.2	2.0	7.1	2.1	8.8	1.4	7.7
COD (mg/l) ^{1, 2}	17.7	45	14.4	55	12.4	45	13	59
Dissolved Oxygen (mg/l) 1,2	8.49	9.98	10.56	11.68	8.51	12.99	9.80	12.97
Dissolved Oxygen Saturation (%) 1,2	67.4	85.1	83.7	93.5	65.2	80.1	75.3	87.5
Propylene Glycol (mg/l) 1, 2	ND	ND	ND	ND	ND	ND	ND	ND

during the 48 hours of sampling. ¹ Results reported as average monthly were determined using the arithmetic average of measurements made every 4 hours

² Results reported as maximum daily were the maximum samples collected every 4 hours during the 48 hours of sampling. BOD_5 Biological oxygen demand 5-day test

COD Chemical oxygen demand

mg/l milligrams per liter

ND - Non-Detect

TABLE 7 FIELD ANALYTICAL RESULTS BUCKEYE BROOK T.F. GREEN AIRPORT WARWICK, RHODE ISLAND FIRST QUARTER 2021

49.8		48.2		44.2		54.2		Temperature (°F)
7.9	5.45	7.23	5.03	7.89	6.20	7.94	5.74	рH
Daily ²	Daily¹	Daily ²	Daily¹	Daily ^a	Daily ¹	Daily ²	Daily¹	
Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Parameter
BB-07	BE	-04	BB-0	BB-03	ВВ	-02	BB-02	

Bold text indicates exceedance of permit standards

every 4 hours during the 48 hours of sampling. Results reported as maximum daily was the maximum flow ¹ Results reported as average monthly were determined using the arithmetic average of measurement made measurements over the 12 hours of sampling.

sampling. ² Results reported as maximum daily were the maximum of the 12 samples collected during the 48 hours of